




# ZONO™ SC 2 DD WD Double Door Double Deep Cabinet with Drying



## YOUR TRUSTED PARTNER IN DISINFECTING+ & SANITIZING\*

- EFFECTIVE** The ZONO™ Cabinet disinfects and sanitizes many different surfaces, including plastics, electronics, metal, and varnished wood; and sanitizes fabrics and other porous surfaces without using liquid chemicals.
- SIMPLE** The ZONO™ Cabinet is simple to set up and easy to operate. Place items onto the Integrated Mobile Carts and roll them directly into the ZONO™ Cabinet. No user assistance is needed during operation, and in 38 minutes, items are ready to use immediately, with no rinsing, wiping, or worry.
- SAFETY FEATURES** Numerous safety features exist to provide protection during operation:
  - Emergency stop buttons inside and outside
  - Clear safety glass panel doors
  - Password protected digital display panel
  - Ozone sensors
  - Magnetic door lock
  - Ozone rated door gaskets
- SUSTAINABLE**
  - The ZONO™ uses three cents of electricity per cycle
  - The ZONO™ uses less than one ounce of water per cycle\*\*

## KILLS 99.9% OF COMMON VIRUSES+ & BACTERIA\* IN 38 MINUTES (Tested by Certified Independent Laboratories)

- ✓ Norovirus
- ✓ Influenza-A
- ✓ Respiratory Syncytial Virus (RSV)
- ✓ Staphylococcus aureus (Staph)
- ✓ Methicillin-Resistant Staphylococcus aureus (MRSA)
- ✓ Escherichia coli (E. coli)
- ✓ Streptococcus pyogenes (S. pyogenes)
- ✓ Shigella dysenteriae (Shigella)
- ✓ Salmonella enteritidis (Salmonella)
- ✓ Pseudomonas aeruginosa (P. aeruginosa)

## SPECIFICATIONS

- Ozone and humidity are generated in the airtight cabinet to disinfect and sanitize.
- Dry cycle dries apparel and gear without damage.
- Exterior meets ASTM C1055 standards. Safe to touch during operation.
- Dimensions: 80" H x 52 5/8" W x 62" D.
- Capacity: 113.6 cu ft.
- Weight: 496 lbs.
- No downtime between cycles.
- Requires NEMA 14-30R 240V Receptacle on Dedicated 30A 2 Phase Circuit.
  - Sanitizing Cycle Max Watts: 800
  - Dry Cycle Max Watts: 3200
- Proudly made in the USA in a U.S. EPA registered facility.



Requires NEMA 14-30R 240V Receptacle on Dedicated 30A 2 Phase Circuit.

## EASE OF USE FEATURES

- ERGONOMIC** The Integrated Mobile Cart System alleviates the need for bending and lifting.
- FAST** Cycles last only 38 minutes. No delay between cycles.
- POWER** No hardwiring, only requires plug-in electrical outlet.
- OPERATION** Simple operating panel.
- GUARANTEE** Includes a three-year warranty for parts and labor.

## OTHER MODELS AVAILABLE

- SC 2 DD** Without optional drying cycle.
- SC 2 DD WH** Heat cycle kills lice, bedbugs and their eggs (125°F).

## ACCESSORIES

- RR 10** 10-bin Cart
- GC** Garment Cart
- HC 3M 48** Helmet Cart
- SD 16** Shoe Dryer
- 4S UC** 4-shelf Utility Cart
- 4S D UC** 4-shelf Deep Utility Cart
- PC 2M 22** Pad Cart